

# SHIELDCOAT TECHNICAL DATA SHEET

## SHIELDSEAL GTP

### DESCRIPTION

**Shieldseal GTP** is a cutting-edge water-based primer that guarantees exceptional adhesion to both glazed and unglazed terracotta roof tiles. Developed with state-of-the-art adhesion promoters, it stands as the most advanced undercoat available. Once cured, Shieldseal GTP creates an incredibly strong bond with the tile surface, ensuring it remains firmly in place and resistant to scratches or damage.

**Light pink liquid- Dries milky**

**Available in 15L pails**

### APPLICATION GUIDE

- Shieldseal GTP is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Shieldseal GTP is designed to be airless sprayed using a 521 or similar spray tip.
- Allow 24-48 hours curing time before re-coating to allow adhesion to build

<h2>SHIELDSEAL GTP</h2>	<p><b>COVERAGE:</b> 6sqm/Lt</p> <p><b>SOLIDS:</b> 55% ave</p> <p><b>WFT:</b> 180um</p> <p><b>DFT:</b> 100um</p> <p><b>TOUCH DRY:</b> 30 Mins</p> <p><b>RECOAT:</b> 24 Hours</p> <p><b>SHELF LIFE:</b> 24 Months</p> <p><b>CLEAN UP:</b> Water</p>
<div><div><p><b>MAX</b> MAXIMUM ADHESION</p></div><div><p><b>WATER BASED</b></p></div><div><p><b>MOULD RESISTANT</b></p></div><div><p><b>DRINKING WATER SAFE</b></p></div></div>	

**DISCLAIMER:** Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



**SHIELDCOAT**